

FLECK[®] 3 00

3 4 - 4 - - -









FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 250 GPM with a backwash of 100 GPM

Backwash capability accommodates softener tanks up to 63" and filter up to 42" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Designed for single or multiple tank systems

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Time-tested, hydraulically-balanced piston for service and regeneration

Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

OPTIONS

Filter or softener control valves
Downflow co-current or upflow
counter-current regeneration
No hard water bypass piston
Brine cam auxiliary switch
Electromechanical timer auxiliary
switch

Treated water regeneration Versatile top or side mount Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration **NXT-** Network controller uses onboard communication capabilities to link multiple valves (via off-the-shelf CAT3, CAT5, or better cables) for system types 4,5,6,7,9,and 14

XT- Offers a two-line, 16 character LCD backlit display for easy entering of master and user programing as well as view of diagnostics

Electromechanical Timer - Simple to adjust and easy to service with quick access to all internal components



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 61 Section 8 Material Safety Only.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

Valve Material Lead-free brass* Inlet/Outlet 3" NPTF/BSPF

Cycles 3 or 5

FLOW RATES (50 PSI INLET) - VALVE ALONE

250 GPM (56.8 m³/h) Continuous

15 psi drop

325 GPM (73.8 m³/h) Peak

25 psi drop

Cv 65

flow at 1 psi drop

Max. Backwash 100 GPM (22.7 m³/h)

25 psi drop

REGENERATION

Downflow/Upflow Both



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 WWW.PENTAIRAQUA.COM CUSTOMER CARE: 800.279.9404 tech-support@pentair.com

is continued to the engineers of the continued of the continued of the engineers of the engineers of the continued of the engineers of the en